

Project	Type	Notes
---------	------	-------

# MHT LIGHTING

## LINE VOLTAGE FIXTURE



Optional Closed Eyelid

## MHTL-WS LED ROUND WALLPACK SERIES

### FEATURES

- Standard 0-10V Dimming Driver
- Available Integrated Button Type Photocell
- Available Integrated Emergency Battery Backup
- Available Integrated Microwave Occupancy Sensor
- Operating Frequency 50Hz/60Hz
- 6kV Line to Line Surge Protection

### GENERAL INFORMATION

Applications	Building Exterior / Garage / Security Lighting / Walkway
Warranty	10-Year Limited Warranty
Construction	Die Cast Aluminum Housing (Dark Bronze) • Borosilicate Glass Lens or Frosted PC Lens • Ceiling or Wall Surface Mounted • Open Bezel or Closed Eyelid Design


### Certifications




### PRODUCT DATA

Universal Input Voltage	120 - 277V
Optional Input Voltage	347V/480V
Power Factor	> 0.93 @277V
Mounting	Multiple Mounting Options
Lumens	> 4,500 Lumens
Max Input Power	48W
CRI	> 80
CCT	3000K/4000K/5000K
L80	> 80,000 Hours
Rated Lifespan	> 100,000 Hours
THD	< 15% @277V

### DIMENSIONS



Open Bezel with Borosilicate Glass Lens  
Standard 1 ft. Leads from the Back



Mounting Bolt Patterns: 8 1/4" X 8 1/4" Hole Size: 5/16"

### FIXTURE PERFORMANCE

Model	Input Power	Color Temp	Lm/W	Lumens	Lens	Dimensions
MHTL-WS-36E-4K-U	36W	4000K	>95	>3,400	PC	Ø15" x 6.65"
MHTL-WS-48E-4K-U	48W	4000K	>95	>4,500	PC	Ø15" x 6.65"

### ORDERING INFO: Sample Code - MHTL-WS-36E-4K-U-CE-GL-CM-PC



Series	Wattage	Color Temperatures	Input Voltage	Distribution	Lens	Mounting	Options
MHTL-WS	E						
MHTL-WS	36=36W 48=48W	3K=3000K 4K=4000K 5K=5000K	U=120-277V 347=347V 480=480V	CE=Closed Eyelid OB=Open Bezel	GL=Glass PL=PC	CM=Ceiling WM=Wall	(Blank) - Custom Color Available. Standard in Dark Bronze PC=Button Type Photocell EB=Emergency Backup SPD=Surge Protective Device OS=Occupancy Sensor